



Declaration of Performance
(according to regulation EU No 305/2011)

Unique identification code of the product-type:
No. BS Section S355J2

Section S355J2 / 1.0577 according EN 10025-2

Intended use:
To be used in Metal Structures and Composite Metal and Concrete Structures

Manufacturer:
British Steel Limited
Brigg Road
Scunthorpe, DN16 1XA

Tel: +44 (0)1724 404040

Website : www.britishsteel.co.uk

System of assessment and verification of constancy of performance of the product:
System 2+

Factory Production Control Notified Body No. 0343 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of conformity of the factory production control.

The performance of the product identified in the Declared Performance is in conformity with the set of declared performance/s.

This declaration of performance is issued, in accordance with: Regulation EU No 305/2011 under the sole responsibility of the manufacturer identified above.

Certificate No. 0343/CPR/LRQ0860859/1

Signed for and on behalf of the manufacturer by:

Chris Vaughan
SHEQ Director,
British Steel Limited

1st April, 2024
Date

Essential characteristic	Declared Performance				Harmonised Standard
Tolerances on dimensions and shape	I & H Sections		EN 10034		EN10025-1 2004
	Equal Flange Tee		EN 10055		
Equal Angle		EN 10056-2			
Unequal Angle		EN10056-2			
Tapered Flange I		EN 10024			
Bulb Flats		EN 10067			
Channels		EN 10279			
Yield strength (transverse)	Nominal thickness (mm)		Values Min (MPa)		
	>	<=			
	-	16	355		
	16	40	345		
	40	63	335		
	63	80	325		
	80	100	315		
100	150	295			
Tensile strength (transverse)	Nominal thickness (mm)		Values (MPa)		
	>	<=	min	max	
	3	100	470	630	
	100	150	450	600	
Elongation (transverse)	Nominal thickness (mm)		Values min (% 5.65√s ₀)		
	>	<=			
	3	40	22		
	40	63	21		
	63	100	20		
100	150	18			
Impact strength (longitudinal)	J2		27J at - 20oC		
Weldability CEV	Nominal thickness (mm)		Values max (%)		
	>	<=			
	-	30	0.45		
	30	40	0.47		
	40	150	0.47		
Durability	Nominal thickness (mm)		Values min (%)	Values max (%)	
	-	40		Mn: 1.60 Cu: 0.55 C: 0.20 (>30mm 0.22) Si: 0.55 P: 0.025 S: 0.025	
	40	150		Mn: 1.60 Cu: 0.55 C: 0.22 Si: 0.55 P: 0.025 S: 0.025	



0343

Manufacturer:
British Steel Limited
Brigg Road
Scunthorpe, UK

20

Unique identification code of the product-type:
BS Section S355J2

Harmonised Standard :
EN 10025-1 – 2004

Section S355J2 / 1.0577

Intended use:
To be used in Metal Structures and Composite Metal and Concrete Structures

Elongation :
Tensile Strength :
Yield Strength : EN 10025-2
Impact Strength :
Weldability :
Durability :

Dangerous Substances : No Performance Determined

EU Notified Body
LRQA Nederland B.V.
George Hintzenweg 77, 3068 AX
Rotterdam, Netherlands
Tel : +31 (0)10 2248500
Email : marc.verboon@lrqa.com
Website : www.lrqa.com