



0343

Declaration of Performance
(according to regulation EU No 305/2011)

Process:
Shot blasted material to ISO 8501 Sa 2.5
& Primer Painted

Intended use:
Structural Steel components, comprising Sections, Hollow Sections & Plates for use in
Building & Construction up to EXECUTION CLASS 4

Manufacturer:

<p>British Steel Limited Teesside Processing & Logistics Lackenby Works, Middlesbrough, Teesside, United Kingdom TS6 7RP</p> <p>Tel: +44 (0)1642 405040</p>	<p>British Steel Limited Lisburn Service Centre Moir Road Lisburn Northern Ireland BT28 2SN</p> <p>Tel: +44 (0)2892 448208</p>
<p>Website : www.britishsteel.co.uk</p>	

EU

Notified Body:

LRQA Nederland B.V,
George Hintzenweg 77, 3068 AX
Rotterdam, Netherlands
Tel : +31 (0)10 2248500
Website : www.lrqa.com

System of assessment and verification of constancy of performance of the product:
EN 1090-1 up to Execution Class 4

Factory Production Control Notified Body No. 0343 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of conformity of the factory production control.

The performance of the product identified in the Declared Performance is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with: Regulation EU No 305/2011, under the sole responsibility of the manufacturer identified above.

Lisburn Service Centre: Certificate No. 0343/CPR/LRQ0860859/2
Teesside Processing & Logistics: Certificate No. 0343/CPR/LRQ0860859/3

Signed for and on behalf of the manufacturer by:

Chris Vaughan
Chief Operating Officer (Interim),
British Steel Limited

23rd January, 2026
Date

Essential characteristic	Declared Performance	Harmonised Standard
Year in which the CE marking was affixed 26		
Tolerances on dimensions and shape	All materials listed in EN1090-2: 2018 + A1: 2024 Class 2	EN 1090-1:2009+A1:2011
Weldability	Welding and Allied processes (ISO 4063) All materials listed in EN 10025 Parts 2 / 4 / 5 No Welding Activity at Process	
Fracture toughness / impact resistance	NPD – results as per Base Material Specification	
Load bearing Capacity	NPD	
Fatigue Strength	NPD	
Resistance to Fire	NPD	
Reaction to Fire	Class A1 (Steel Only)	
Release of Cadmium and its compounds	NPD	
Radioactivity	NPD Radioactivity in Steel Statement Available from www.BritishSteel.co.uk	
Dangerous Substances	NPD	
Durability	Surface preparation to BS EN 1090-2 Preparation grade P3, Surface painted to Customer Specific Requirements: Thickness Range: 20 – 75 microns Weldable corrosion primer coating; Colour: Red or Grey Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) No 453/2010	