



Declaration of Performance
The Construction Products (Amendment etc.) (EU Exit)
Regulations 2020 No 1359

Unique identification code of the product-type:
 No. BS Section S275J2

Section S275J2 / 1.0145 according EN 10025-2

Intended use:
 To be used in Metal Structures and Composite Metal and
 Concrete Structures

Manufacturer:
British Steel Limited
Brigg Road
Scunthorpe, DN16 1XA

Tel: +44 (0)1724 404040

Website : www.britishsteel.co.uk

System of assessment and verification of constancy of
 performance of the product:
System 2+

Factory Production Control Assessment body No. 0038 performed the initial
 inspection of the manufacturing plant and of factory production control and the
 continuous surveillance, assessment, and evaluation of factory production
 control and issued the certificate of conformity of the factory production control.

The performance of the product identified in the Declared Performance is in
 conformity with the set of declared performance/s.
 This declaration of performance is issued, in accordance with: Regulation (EU
 Exit) Regulations 2020 No 1359, under the sole responsibility of the
 manufacturer identified above.

Certificate No. 0038/CPR/LRQ0860859/1

Signed for and on behalf of the manufacturer by:

Chris Vaughan
 Chief Operating Officer (Interim),
 British Steel Limited

1st May 2025
 Date

Essential characteristic	Declared Performance				Harmonised Standard
	Nominal thickness (mm)		Values (MPa)		
Tolerances on dimensions and shape	I & H Sections		EN 10034		EN10025-1 2004
	Equal Flange Tee		EN 10055		
	Equal Angle		EN 10056-2		
	Unequal Angle		EN10056-2		
	Tapered Flange I		EN 10024		
	Bulb Flats		EN 10067		
	Channels		EN 10279		
Yield strength (transverse)	Nominal thickness (mm)		Values (MPa)		EN10025-1 2004
	>	<=	Min		
	-	16	275		
	16	40	265		
	40	63	255		
	63	80	245		
	80	100	235		
100	150	225			
Tensile strength (transverse)	Nominal thickness (mm)		Values (MPa)		EN10025-1 2004
	>	<=	min	max	
	3	100	410	560	
	100	150	400	540	
Elongation (transverse)	Nominal thickness (mm)		Values min (% 5.65√s ₀)		EN10025-1 2004
	>	<=			
	3	40	23		
	40	63	22		
	63	100	21		
	100	150	19		
Impact strength (longitudinal)	J2		27J at - 20°C		
Weldability CEV	Nominal thickness (mm)		Values max (%)		EN10025-1 2004
	>	<=			
	-	40	0.40		
	40	150	0.42		
Durability	Nominal thickness (mm)		Values min (%)	Values max (%)	EN10025-1 2004
	-	150		Mn: 1.50 Cu: 0.55 C: 0.18 P: 0.025 S: 0.025	



0038

Manufacturer:
British Steel Limited
Brigg Road
Scunthorpe, UK

20

Unique identification code of the product-type:
BS Section S275J2

Harmonised Standard :
 EN 10025-1 – 2004

Section S275J2 / 1.0145

Intended use:
 To be used in Metal Structures and Composite Metal
 and Concrete Structures

Elongation :
 Tensile Strength :
 Yield Strength : EN 10025-2
 Impact Strength :
 Weldability :
 Durability :

Dangerous Substances : No Performance Determined

UK Conformity Assessment Body
LRQA Verification Limited
1 Trinity Park, Bickenhill Lane,
Birmingham B37 7ES.

Website www.lrqa.com